



Defoamer

Better BWP-5115

Product Description:

Better BWP-5115 Defoamer is suitable for a wide range of lotion coatings, inks and adhesives, with durable defoaming ability and good shear stability. Good storage stability, long-term storage, maintaining good defoaming properties, strong defoaming ability, and good durability.

Product Features:

- Suitable for latex paint and latex systems;
- Excellent defoaming and anti foaming effect;
- Good compatibility;
- High safety;
- No adverse effect on gloss.

Product specifications:

Appearance	Milky white liquid
Ionicity	non-ionic
Activity content	50 ± 1
Viscosity (25 °C)	100~1000mPa · s
Water solubility	dispersible

Product application field: coating

use to:

- Various latex systems.
- Styrene, butadiene, acrylic acid, polyvinyl chloride and their copolymers.
- Water-based adhesive.
- Polyvinyl alcohol system.

Addition amount and usage method:

- It can be directly added during the production and manufacturing process or pre dispersed for use.
- Generally, 0.2-0.3% of the total formula can effectively extinguish and prevent the regeneration of foam.
- If used as an adhesive, the addition amount is 1-2% of the solid amount of the latex.
- Layering may occur and should be thoroughly stirred before use.

Packaging specifications and storage:

25kg/ 50kg/ 200kg Plastic bucket packaging or 1000kg IBC bucket.



Store at room temperature (5 °C -40 °C), avoid direct sunlight, with a warranty period of 6 months.

Heavy metal content:

Content	Sb	As	Ba	Cd	Cr	Pb	Hg	Se	Zn
ppm	<5	<2.5	<10	<5	<5	<5	<5	<5	<10